



**100% durable modified plywood**

*Resistance that challenges nature*



- **ULTRA-DURABLE PANEL FOR OUTDOOR APPLICATION**
- **SUSTAINABLE EUROPEAN PLANTATION WOOD**
- **LIGHTWEIGHT & EASY-TO-MACHINE**
- **STABILITY & DIMENSIONAL UNIFORMITY**



The mark of  
responsible forestry  
This logo only refers  
to FSC MIX CREDIT  
products



**garnica**

Challenge the ordinary



**100% durable modified plywood**

*Resistance that challenges nature*

Finishes available:

HPL

MDO

PRM

XPS

CPL

## Product description:

Ultra-durable panel for outdoor use in the most demanding conditions, composed of sustainable plantation wood.

Plywood modified using an innovative treatment renders the entire panel exceptionally durable. Immune to fungal and insect attack, even when used outdoors and in the most demanding of weather conditions.

Its CE2 + structural certificate, lightness, surface quality and ease of machining makes it perfect for facades and other construction applications.

Maximum sustainability due to its composition based on fast growing European plantation wood.

**Glue Type:** Class III (exterior) according to the rule EN 636

**Emission:** Class E1 according to the rule EN 13986

**Quality faces:** BB/BB

## Applications/Uses:

Perfect for external applications: sandwich panels, light lattice construction, advertising panels, message signs/panels, facades, roof supports, ledges, gardening, parks, recreational areas, street furniture, etc.

### Formats

Dimensions mm	2500x1220									
Thickness mm	9	10	12	15	18	22	25	30	40	
No. of plies	5	5	7	7	9	11	11	13	17	
Dimensions mm	3100x1530									
Thickness mm	9	12	15	18	22	25	30	40		
No. of plies	5	7	7	9	11	11	13	17		

*Formats may vary without notice. Please contact your local sales manager to check the availability in your region.*

### Technical features

	Values	Standard
Density (Kg/m <sup>3</sup> )	440-500	UNE EN 323
MOE - Modulus of elasticity (N/mm <sup>2</sup> )	3.400-5.500	UNE EN 310
Face Screw Holding (kgf)	135	UNE EN 320
Moisture content (%)	6-14	UNE EN 322

Wood is a natural material and as such is unique in appearance & so often has naturally occurring variations in color, texture and grain pattern. The photographic reproductions used simply provide an example of a product's appearance & may not be representative of the full range of color, texture and grain variations. The data provided in this product specification should be used solely as a guide & is of no contractual value. It is the responsibility of the acquirer to determine if the product is suitable for the required application, to ensure that both the place & form of use are appropriate & in accordance with the manufacturer's requirements & recommendations & is in line with current regulations.

**Edges must be carefully sealed in order to ensure proper seal of the panels when used for exterior applications.**



CE CE2+

**garnica**

Challenge the ordinary

Parque de San Miguel, 10 - bajo  
26007 Logroño, La Rioja  
Spain  
Tel.: +34 941 51 23 55  
Fax: +34 941 51 23 57  
sales@garnica.one  
www.garnica.one